

Door Enclosures

Range: Enclosures

Order Code: EDE-PLA-020-030-013-GL (DED001)



DESCRIPTION

IP65, IK08 Lockable solid door plastic enclosure 300x200x130

ENCLOSURES FEATURES

- Available in 10 sizes
- Made from UL approved ABS-HB Flame Retardant plastic
- Designed to meet protection and combustibility standards IP65 and IK08
- Comes complete with steel back plate and mounting brackets
- Supplied in grey (RAL 7035) body with solid or transparent door
- Suitable for use in sea salt air conditions and dry dust environments
- Temperature range of -20° to +85°

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.

SPECIFICATION

Product Type	Solid door enclosures
Door Style	Solid
Enclosure Material	ABS-HB
Door Material	ABS-HB
IP Rating	65
Colour	Grey (RAL 7035)
Min Temperature Rating °C	-20
Max Temperature Rating °C	85
Height (mm)	300
Width (mm)	200
Depth (mm)	130
Mounting Plate (mm)	143x250x1
Number of Locks	1
Comments	Lockable, with galvanized steel back plate and wall mounting brackets supplied
Accessories Available	Kwik fix cable gland

INDUSTRY ACCREDITATIONS

