

# Door Enclosures

## Range: Enclosures

Order Code: EDE-PLA-025-035-015-GL (DED002)



### DESCRIPTION

IP65, IK08 Lockable solid door plastic enclosure 350x250x150

### ENCLOSURES FEATURES

- Available in 10 sizes
- Made from UL approved ABS-HB Flame Retardant plastic
- Designed to meet protection and combustibility standards IP65 and IK08
- Comes complete with steel back plate and mounting brackets
- Supplied in grey (RAL 7035) body with solid or transparent door
- Suitable for use in sea salt air conditions and dry dust environments
- Temperature range of -20° to +85°

*Subject to technical modification without notice.*

*Typographical and other errors do not justify claim for damages.*

## SPECIFICATION

<b>Product Type</b>	Solid door enclosures
<b>Door Style</b>	Solid
<b>Enclosure Material</b>	ABS-HB
<b>Door Material</b>	ABS-HB
<b>IP Rating</b>	65
<b>Colour</b>	Grey (RAL 7035)
<b>Min Temperature Rating °C</b>	-20
<b>Max Temperature Rating °C</b>	85
<b>Height (mm)</b>	350
<b>Width (mm)</b>	250
<b>Depth (mm)</b>	150
<b>Mounting Plate (mm)</b>	193x300x1
<b>Number of Locks</b>	2
<b>Comments</b>	Lockable, with galvanized steel back plate and wall mounting brackets supplied
<b>Accessories Available</b>	Kwik fix cable gland

## INDUSTRY ACCREDITATIONS

