

Door Enclosures

Range: Enclosures

Order Code: EDE-PLA-025-035-015-GT (DED012)



DESCRIPTION

IP65, IK08 Lockable transparent door plastic enclosure 350x250x150

ENCLOSURES FEATURES

- Available in 10 sizes
- Made from UL approved ABS-HB Flame Retardant plastic
- Designed to meet protection and combustibility standards IP65 and IK08
- Comes complete with steel back plate and mounting brackets
- Supplied in grey (RAL 7035) body with solid or transparent door
- Suitable for use in sea salt air conditions and dry dust environments
- Temperature range of -20° to +85°

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.

SPECIFICATION

Product Type	Transparent door enclosures
Door Style	Transparent
Enclosure Material	ABS-HB
Door Material	Polycarbonate
IP Rating	65
Colour	Grey (RAL 7035)
Min Temperature Rating °C	-20
Max Temperature Rating °C	85
Height (mm)	350
Width (mm)	250
Depth (mm)	150
Mounting Plate (mm)	193x300x1
Number of Locks	1
Comments	Lockable, with galvanized steel back plate and wall mounting brackets supplied
Accessories Available	Kwik fix cable gland

INDUSTRY ACCREDITATIONS

