

# Screwless - Push Wire

Range: PCB Terminal Blocks, Connectors and Fuse Holders

Order Code: TLM303-02P



## DESCRIPTION

2 Pole Spring - Screwless Tool operated Wave - through hole 45 degree 5.08mm pitch 15A 300V

*Subject to technical modification without notice.*

*Typographical and other errors do not justify claim for damages.*

## SPECIFICATION

|                                  |                                                                       |
|----------------------------------|-----------------------------------------------------------------------|
| <b>Type</b>                      | Spring - Screwless                                                    |
| <b>Connection Method</b>         | Tool operated                                                         |
| <b>Mounting Type</b>             | Wave - through hole                                                   |
| <b>Orientation</b>               | 45 degree                                                             |
| <b>Join</b>                      | End stackable                                                         |
| <b>Pitch (mm)</b>                | 5.08                                                                  |
| <b>Number of Poles</b>           | 2                                                                     |
| <b>Min Wire Size (Sq mm)</b>     | 0.08                                                                  |
| <b>Max Wire Size (Sq mm)</b>     | 2.5                                                                   |
| <b>Max Current (A)</b>           | 15                                                                    |
| <b>Max Voltage (V)</b>           | 300                                                                   |
| <b>Height (mm)</b>               | 13                                                                    |
| <b>Standard Colour</b>           | Grey                                                                  |
| <b>Width (mm)</b>                | 14.3                                                                  |
| <b>Length (mm)</b>               | 11.16                                                                 |
| <b>Solder Pin Length (mm)</b>    | 4                                                                     |
| <b>PCB Hole Diameter (mm)</b>    | 1.2                                                                   |
| <b>Approvals Pending</b>         | UL Pending                                                            |
| <b>Body Material</b>             | PA66 V0                                                               |
| <b>Comments</b>                  | Pole sizes / no of ways not shown, please contact us for availability |
| <b>Min Temperature Rating °C</b> | -40                                                                   |
| <b>Max Temperature Rating °C</b> | 105                                                                   |
| <b>Min Wire Size AWG</b>         | 28                                                                    |
| <b>Max Wire Size AWG</b>         | 12                                                                    |