


Pluggable Pin Header (Male) -Single Row PCB Header

Range: PCB Terminal Blocks, Connectors and Fuse Holders

Part Number: TLPHC-100V-02P



DESCRIPTION

2 Pole PCB mount - Male header Wave - through hole Vertical 3.81mm pitch 8A(UL)/10A(VDE) 300V(UL) 150V(VDE)

Subject to technical modification without notice. Typographical and other errors do not justify claim for damages.



MAKING THE RIGHT CONNECTIONS

SPECIFICATION

Туре	PCB mount - Male header
Mounting Type	Wave - through hole
Orientation	Vertical
Join	Solid body non stackable
Pitch (mm)	3.81
Open/Closed/Screw/Flange	Closed End
Number of Poles	2
Max Current (A)	8A(UL)/10A(VDE)
Max Voltage (V)	300V(UL) 150V(VDE)
Height (mm)	9.2
Standard Colour	Green
Width (mm)	7
Length (mm)	8.41
Solder Pin Length (mm)	3.5
PCB Hole Diameter (mm)	1.4
Body Material	PA66 V0
Commente	Pole sizes / no of ways not shown, please contact us for availability
Comments Min Temperature Rating °C	-40
Max Temperature Rating °C	105

INDUSTRY ACCREDITATIONS



MAKING THE **RIGHT** CONNECTIONS **WWW.HYLEC-APL.COM | SALES@HYLEC-APL.COM | 01933 234400**

