


## Pluggable Pin Header (Male) -Single Row PCB Header

# Range: PCB Terminal Blocks, Connectors and Fuse Holders

Order Code: TLPHC-400R-05P



### DESCRIPTION

5 Pole PCB mount - Male header Wave - through hole Horizontal 7.5mm pitch 16A(UL)/15A(VDE) 300V(UL) 450V(VDE)

Subject to technical modification without notice. Typographical and other errors do not justify claim for damages.



## MAKING THE **RIGHT** CONNECTIONS

### **SPECIFICATION**

Туре	PCB mount - Male header
Mounting Type	Wave - through hole
Orientation	Horizontal
Join	Solid body non stackable
Pitch (mm)	7.5
Open/Closed/Screw/Flange	Closed End
Number of Poles	5
Max Current (A)	16A(UL)/15A(VDE)
Max Voltage (V)	300V(UL) 450V(VDE)
Height (mm)	8.6
Standard Colour	Green
Width (mm)	12
Length (mm)	37.5
Solder Pin Length (mm)	4
PCB Hole Diameter (mm)	1.6-1.7
Body Material	PA66 V0
Commente	Pole sizes / no of ways not shown, please contact us for availability
Comments Min Temperature Rating °C	-40
Max Temperature Rating °C	105

## **INDUSTRY ACCREDITATIONS**



MAKING THE **RIGHT** CONNECTIONS WWW.HYLEC-APL.COM | SALES@HYLEC-APL.COM | 01933 234400

