


# Contactors

## Range: Motor Control Gear

Order Code: DEC-45D11/110VAC



### DESCRIPTION

3 pole contactor, AC1 60A, 110V AC coil

### MOTOR CONTROL GEAR FEATURES

- CSA, CE, UL(listed)
- C/W instantaneous auxiliary contact
- Temperature range of -20°C to +85°C
- Combi Head Ready to Tighten Screws
- Compact design
- Heavy duty pure silver point contact
- IP20 finger protected screws

*Subject to technical modification without notice.*

*Typographical and other errors do not justify claim for damages.*

## SPECIFICATION

<b>Weight</b>	1.1
<b>Length (mm)</b>	129.3
<b>Width (mm)</b>	75
<b>Height (mm)</b>	115
<b>AC1 duty <math>\varnothing</math> less than/equal 40°C</b>	60
<b>Three Phase Load at 240V (kW)</b>	15
<b>Three Phase Load at 380V (kW)</b>	30
<b>Three Phase Load at 400V (kW)</b>	30
<b>Three Phase Load at 440V (kW)</b>	30
<b>Three Phase Load at 575V (kW)</b>	30
<b>Aux Contact Number</b>	2
<b>Aux Contact Type</b>	N/O + N/C
<b>Series</b>	DEC
<b>Voltage (VAC)</b>	110