

Contactors

Range: Motor Control Gear

Order Code: DEC-25D10/240VAC



DESCRIPTION

3 pole contactor, AC1 40A,240V AC coil

MOTOR CONTROL GEAR FEATURES

- CSA, CE, UL(listed)
- C/W instantaneous auxiliary contact
- Temperature range of -20°C to +85°C
- Combi Head Ready to Tighten Screws
- Compact design
- Heavy duty pure silver point contact
- IP20 finger protected screws

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.

SPECIFICATION

| | |
|---|-------|
| Weight | 0.525 |
| Length (mm) | 77 |
| Width (mm) | 56.5 |
| Height (mm) | 95.5 |
| AC1 duty \varnothing less than/equal 40°C | 40 |
| Three Phase Load at 240V (kW) | 7.5 |
| Three Phase Load at 380V (kW) | 15 |
| Three Phase Load at 400V (kW) | 15 |
| Three Phase Load at 440V (kW) | 15 |
| Three Phase Load at 575V (kW) | 15 |
| Single Phase Load at 120V (kW) | 2.2 |
| Single Phase Load at 240 V (kW) | 4 |
| Aux Contact Number | 1 |
| Aux Contact Type | N/O |
| Series | DEC |
| Voltage (VAC) | 240 |

INDUSTRY ACCREDITATIONS

