



Door Enclosures

Range: Enclosures

Part Number: DED3013



DESCRIPTION

IP65, IK08 Lockable transparent door plastic enclosure 500x400x175

ENCLOSURES FEATURES

- Available in 10 sizes
- Made from UL approved ABS-HB Flame Retardant plastic
- Designed to meet protection and combustibility standards IP55 and IK08
- Comes complete with steel back plate and mounting brackets
- Supplied in grey (RAL 7035) body with solid or transparent door
- Suitable for use in sea salt air conditions and dry dust environments
- Temperature range of -20° to +85°

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.

SPECIFICATION

| | |
|----------------------------------|--|
| Product Type | Transparent door enclosures |
| Door Style | Transparent |
| Enclosure Material | ABS-HB |
| Door Material | Polycarbonate |
| IP Rating | 65 |
| Colour | Grey (RAL 7035) |
| Min Temperature Rating °C | -20 |
| Max Temperature Rating °C | 85 |
| Height (mm) | 500 |
| Width (mm) | 400 |
| Depth (mm) | 175 |
| Mounting Plate (mm) | 345x452x1 |
| Number of Locks | 2 |
| Comments | Lockable, with galvanized steel back plate and wall mounting brackets supplied |
| Accessories Available | Kwik fix cable gland |

INDUSTRY ACCREDITATIONS

