

# Door Enclosures

## Range: Enclosures

Part Number: DED3021



### DESCRIPTION

IP65, IK08 Lockable solid door plastic enclosure 800x600x260

### ENCLOSURES FEATURES

- Available in 10 sizes
- Made from UL approved ABS-HB Flame Retardant plastic
- Designed to meet protection and combustibility standards IP55 and IK08
- Comes complete with steel back plate and mounting brackets
- Supplied in grey (RAL 7035) body with solid or transparent door
- Suitable for use in sea salt air conditions and dry dust environments
- Temperature range of -20° to +85°

*Subject to technical modification without notice.*

*Typographical and other errors do not justify claim for damages.*

## SPECIFICATION

<b>Product Type</b>	Solid door enclosures
<b>Door Style</b>	Solid
<b>Enclosure Material</b>	ABS-HB
<b>Door Material</b>	ABS-HB
<b>IP Rating</b>	65
<b>Colour</b>	Grey (RAL 7035)
<b>Min Temperature Rating °C</b>	-20
<b>Max Temperature Rating °C</b>	85
<b>Height (mm)</b>	800
<b>Width (mm)</b>	600
<b>Depth (mm)</b>	260
<b>Mounting Plate (mm)</b>	560x745x1.2
<b>Number of Locks</b>	3
<b>Comments</b>	Lockable, with galvanized steel back plate and wall mounting brackets supplied
<b>Accessories Available</b>	Kwik fix cable gland

## INDUSTRY ACCREDITATIONS

