

Door Enclosures

Range: Enclosures

Order Code: EDE-PLA-060-080-026-GT (DED3022)



DESCRIPTION

IP65, IK08 Lockable transparent door plastic enclosure 800x600x260

ENCLOSURES FEATURES

- Available in 10 sizes
- Made from UL approved ABS-HB Flame Retardant plastic
- Designed to meet protection and combustibility standards IP55 and IK08
- Comes complete with steel back plate and mounting brackets
- Supplied in grey (RAL 7035) body with solid or transparent door
- Suitable for use in sea salt air conditions and dry dust environments
- Temperature range of -20° to +85°

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.

SPECIFICATION

Product Type	Transparent door enclosures
Door Style	Transparent
Enclosure Material	ABS-HB
Door Material	Polycarbonate
IP Rating	65
Colour	Grey (RAL 7035)
Min Temperature Rating °C	-20
Max Temperature Rating °C	85
Height (mm)	800
Width (mm)	600
Depth (mm)	260
Mounting Plate (mm)	560x745x1.2
Number of Locks	3
Comments	Lockable, with galvanized steel back plate and wall mounting brackets supplied
Accessories Available	Kwik fix cable gland

INDUSTRY ACCREDITATIONS

