



Pillar Terminal Blocks

Range: Emech Terminals/Accessories

Order Code: CTS-INR-R12-W09 (HY434/9 NYHLP)



DESCRIPTION

9 pole natural polyamide PA6.6 wire protected pillar terminal block 12mm pitch 41a 750v

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.

SPECIFICATION

| | |
|---------------------------------------|--------------------------|
| Number of Poles | 9 |
| Terminal Material | OT58 nickel plated |
| Terminal Type | Wire Protected |
| Body Material | Polyamide PA6.6 |
| Colour | Natural |
| Glow Wire Resistance Test Temp | GWIT775°C (EN60695-2-13) |
| Max Conductor Size (Sq mm) | 6 |
| Max Current (A) | 41 |
| Max Voltage (V) | 750 |
| Working Temperature | 110 |
| Pitch (mm) | 12 |
| Height (mm) | 21.5 |
| Width (mm) | 23.1 |
| Length (mm) | 104.2 |
| Diameter (mm) | 3.2 |
| Flammability Rating | UL94V2 and GWIT775°C |
| Terminal Screw Material | White zinc plated steel |
| Wire Protection Material | Stainless steel |

INDUSTRY ACCREDITATIONS

