

DC Rotary Isolator Switches

Range: Rotary Isolator Switches

Order Code: SRI-EDA-16A-GG (DE1S.04.16DC)



DESCRIPTION

IP66 16A DC Isolator Switch

ROTARY ISOLATOR SWITCHES FEATURES

- IP66 Rated
- AC & DC Range Available
- Silver Plated Alloy Contacts for High Reliability
- Highly Visible & Robust Housing
- 4-Pole Earth terminal Included
- Polycarbonate UL94V-0 Flame Retardant
- Captive Retained Cover Screws
- Can be Padlocked (padlock not included)

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.

SPECIFICATION

| | |
|--|-------|
| Rated insulation voltage (Ui) VAC | 1500V |
| Rated thermal current (Ith) A | 16A |
| Rated impulse without voltage (Uimp) | 8000V |
| Rated short-time with stand current (Icw) 2,4,6,8 | 800A |
| Rated short-time with stand current (Icw) 2H, 3H, 4H | 1300A |
| Rated short-time making capacity (Icm) 2,4,6,8 | 800A |
| Rated short-time making capacity (Icm) 2H, 3H, 4H | 1300A |
| Rated conditional short circuit current (Icc) | 5000A |
| Maximum Fuse Size (gL(gG)) | 40A |