



Micro TeePlug & Sockets

Range: Weatherproof/Waterproof Connectors

Order Code: CWP-PMM-LA-02A (THB.381.N2B)



DESCRIPTION

Micro Plug M16 2 pole Screw terminal IP68/69K 10A 500V 1 cable entry

WEATHERPROOF/WATERPROOF CONNECTORS FEATURES

- Miniaturization \hat{A} - a diameter of only 14mm (2 poles)
- Screw connection for field wiring (M2 screws - max 0.2 Nm) and versatility guaranteed during installation
- Available with overmolded cable
- Tested and approved to resist dust and water (IP68 30m/1h) and high pressure water (IP69K)
- Suitable For Class 2 Applications (Double Insulated) Max. 250V AC.

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.

SPECIFICATION

| | |
|---------------------------|--|
| Type | Plug |
| Cable Entries | 1 |
| Max Current (A) | 10 |
| Max Voltage (V) | 500 |
| Number of Poles | 2 |
| IP Rating | 68/68K |
| Min Temperature Rating °C | -40 |
| Max Temperature Rating °C | 125 |
| Temperature "T" Rating | T125 |
| Body Material | PA66 GF UL94 V0 |
| Fixing System | Cable |
| Terminal Type | Silver-plated brass (zinc-plated screws) |

INDUSTRY ACCREDITATIONS

