



Relays

Range: Relays and Sockets

Part Number: DPRN131.110VAC



DESCRIPTION

110V, 3, Pole 10A Relay

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.

SPECIFICATION

| | |
|-------------------------------------|---|
| Ambient Temperature °C | -40°C - +55°C |
| Number of Poles | 3 |
| Contact Resistance (mOhm) | 100 (1A, 24VDC) |
| Contact Load (Resistance) | NO: 10A 250VAC/28VDC, NC: 5A 250VAC/28VDC |
| Max Switching Voltage | 250VAC/28VDC |
| Max Switching Current | 10A |
| Max Switching Power | 2500VA/280W |
| Insulation Resistance (mOhm) | 500 (500VDC) |
| Operate Time | Max 30ms |
| Release Time | Max 30ms |
| Vibration | 10-55Hz 1mm |
| Operating Humidity | 98%RH, +40°C |
| Termination | Octal & undecal type plug |
| Construction | Dust protected |
| Rated Voltage (VAC) | 110 |
| Pick Up Voltage (VAC) | less than equal to 80.0 |
| Drop Out Voltage (VAC) | more than equal to 30.0 |
| Resistance (mOhm) | 1500±10% |