Micro TeePlug & Sockets

Range: Weatherproof/Waterproof Connectors

Part Number: THK.381.KIT



DESCRIPTION

Micro Plug 2 pole Screw terminal 5.8mm to 8.0mm cable diameter, IP68/IP69K 10A 500V 1 cable entry and Micro Socket 2 pole Screw terminal 5.8mm to 8.0mm cable diameter, IP68/IP69K 10A 500V 1 cable entry

WEATHERPROOF/WATERPROOF CONNECTORS FEATURES

- Miniaturization a diameter of only 14mm (2 poles)
- Screw connection for field wiring (M2 screws max 0.2 Nm) and versatility guaranteed during installation
- Available with overmolded cable
- Tested and approved to resist dust and water (IP68 30m/1h) and high pressure water (IP69K)
- Suitable For Class 2 Applications (Double Insulated) Max. 250V AC.

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.



SPECIFICATION

Туре	Plug & Socket
Cable Entries	1
Max Current (A)	10
Max Voltage (V)	500
Number of Poles	2
Minimum Cable Diameter (mm)	5.8
Maximum Cable Diameter (mm)	6.9
IP Rating	68/68K
Min Temperature Rating °C	-40
Max Temperature Rating °C	125
Temperature "T" Rating	T125
Body Material	PA66 GF UL94 V0
Fixing System	Cable
Terminal Type	Silver-plated brass (zinc-plated screws)

INDUSTRY ACCREDITATIONS



