



# TeePlug & Sockets

## Range: Weatherproof/Waterproof Connectors

Part Number: THB.389.A4E.R

---



---

### DESCRIPTION

Mini Plug, 4 pole Screw terminal THB.389.A4E, 7mm to 13.5mm cable diameter, IP68 rated 17.5A (AC/DC), 500V, 1 cable entry and Micro Socket, 4 pole Screw terminal THB.389.B4E, 6mm to 13mm cable diameter, IP68 rated 17.5A (AC/DC), 500V, 1 cable entry. Cable marking 2-3/L-N-E

### WEATHERPROOF/WATERPROOF CONNECTORS FEATURES

- Miniaturization - a diameter of only 23mm (4 poles)
- Screw connection for field wiring (M2 screws - max 0.2 Nm) and versatility guaranteed during installation
- Available with over-molded cable
- Suitable For Class 2 Applications (Double Insulated) Max. 500V AC.

*Features may vary by product throughout the range.*

*Subject to technical modification without notice.*

*Typographical and other errors do not justify claim for damages.*

## SPECIFICATION

Type	Plug & Socket
Cable Entries	1
Max Current (A)	17.5A AC/DC
Max Voltage (V)	500
Number of Poles	4
Minimum Cable Diameter (mm)	6
Maximum Cable Diameter (mm)	13
IP Rating	IP66/IP68 (5m/1h)/IP69
Min Temperature Rating °C	-40
Max Temperature Rating °C	125
Body Material	PA66 GF UL94 V0
Fixing System	Cable
Terminal Type	Silver-plated brass (zinc-plated screws)

## INDUSTRY ACCREDITATIONS

