


Solar Power Extension Cables

Range: Solar Power Connection

Order Code: CPV-RE5-1T1-B02





DESCRIPTION

A single, Red MC4 Solar PV extension cable, DC to DC, 6mm diameter, length 2 metres with Male & Female CPV-KC5-1T1-I connectors, rated to 1,500V

SOLAR POWER CONNECTION FEATURES

- High Currency/Voltage capacity
- NEC Interlocked
- Contact Material 99.98% pure copper, minimises power loss
- Halogen free XPLO insulation, Virgin PVC sheathing, maximises protection from the elements
- Flame retardant to UV94 V-0
- Highly resitant to high/low temperatures, water, UV light, oxidation, rust, and corrosion

Subject to technical modification without notice. Typographical and other errors do not justify claim for damages.

MAKING THE RIGHT CONNECTIONS

hylec

SPECIFICATION

Connection Method	MC4, Bayonet locking, NEC Interlocked
Max Current (A)	30
Max Voltage (V)	1,500
Colour	Red
IP Rating	IP68
Max Temperature Rating °C	85
Min Temperature Rating °C	-40
UL94 Rating	UL94 V-0
Cable Diameter (mm)	4
Contacts Material	Tin Plated Copper
Length (Metres)	2

INDUSTRY ACCREDITATIONS



