
# Solar Power Extension Cables

Range: Solar Power Connection

Order Code: CPV-BE5-1T1-A10





### **DESCRIPTION**

A single, black MC4 Solar PV extension cable, DC to DC, 4mm diameter, length 10 metres with Male & Female CPV-KC5-1T1-I connectors, rated to 1,500V

### **SOLAR POWER CONNECTION FEATURES**

- · High Currency/Voltage capacity
- NEC Interlocked
- Contact Material 99.98% pure copper, minimises power loss
- Halogen free XPLO insulation, Virgin PVC sheathing, maximises protection from the elements
- Flame retardant to UV94 V-0
- Highly resitant to high/low temperatures, water, UV light, oxidation, rust, and corrosion

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.



## **SPECIFICATION**

Connection Method	MC4, Bayonet locking, NEC Interlocked
Max Current (A)	30
Max Voltage (V)	1,500
Colour	Black
IP Rating	IP68
Max Temperature Rating °C	85
Min Temperature Rating °C	-40
UL94 Rating	UL94 V-0
Cable Diameter (mm)	4
Contacts Material	Tin Plated Copper
Length (Metres)	10

# **INDUSTRY ACCREDITATIONS**





