

# Micro TeePlug & Sockets

### Range: Weatherproof/Waterproof Connectors

Order Code: CWP-PMM-PO-03A (THB.381.N3E)



#### DESCRIPTION

Micro Plug M16 3 pole Screw terminal IP68/69K 10A 500V 1 cable entry

### WEATHERPROOF/WATERPROOF CONNECTORS FEATURES

- · Miniaturization a diameter of only 14mm (3 poles)
- Screw connection for field wiring (M2 screws max 0.2 Nm) and versatility guaranteed during installation
- · Available with overmolded cable
- Tested and approved to resist dust and water (IP68 30m/1h) and high pressure water (IP69K)
- Suitable For Class 2 Applications (Double Insulated) Max. 250V AC.

Subject to technical modification without notice. Typographical and other errors do not justify claim for damages.

## hylec

### MAKING THE RIGHT CONNECTIONS

#### **SPECIFICATION**

Туре	Plug
Cable Entries	1
Max Current (A)	10
Max Voltage (V)	500
Number of Poles	3
IP Rating	68/69K
Min Temperature Rating °C	-40
Max Temperature Rating °C	125
Temperature "T" Rating	T125
Body Material	PA66 GF UL94 V0
Fixing System	Cable
Terminal Type	Silver-plated brass (zinc-plated screws)

### **INDUSTRY ACCREDITATIONS**



MAKING THE **RIGHT** CONNECTIONS WWW.HYLEC-APL.COM | SALES@HYLEC-APL.COM | 01933 234400

