
Emergency Stop Stations

Range: Control Stations

Part Number: 1DE.03.01AB





*Enclosure only except 1DE .SP series where D includes actuator height

DESCRIPTION

E-stop twist to release and 2 black push buttons for up/down, left/right, yellow cover, black base.

CONTROL STATIONS FEATURES

- Customised control station service available please ask for details.
- Insulation resistance >100MOhm @ 500VDC
- Enclosures sealed up to IP56
- Unique snap on Din Rail and Flange brackets
- Dust & waterproof for short-term submersion
- 4 sizes available! Accepting 1-4 push button switches
- · 2 contact blocks fitted as standard
- Different voltage ratings are available
- Contact material Silver Bifurcated and serrated
- Operating Temperature -10 to +65°C
- Contact rating AC12 Resistive / AC15 Electromagnetic 240V (3A) / 415V (1.5A)
- · Mechanical life 1 million operations

Features may vary by product throughout the range.

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.



SPECIFICATION

Accessories Available	DIN rail and flange snap-on brackets	
Base Colour	Black	
Base Style	Standard base	
Depth (mm)	53	
Enclosure Material	ABS-UL94-HB	
Height (mm)	80	
IP Rating	IP56	
Lid Colour	Yellow	
Min Temperature Rating °C	-10	
Max Temperature Rating °C	65	
Number of Switches	3	
Size (mm)	80x139x53	
Switch 1 Style	Pushbutton non-illuminated	
Switch 1 Substyle	Mushroom head	
Switch 2 legend Sticker	UP	
Switch 2 Style	Pushbutton non-illuminated	
Switch 2 Substyle	Flush head	
Switch 3 legend Sticker	DOWN	
Switch 3 Style	Pushbutton non-illuminated	
Switch 3 Substyle	Flush head	
Width (mm)	139	