

# Switches

## Range: Switches and Lamps

Order Code: DLB22-E11YI



### DESCRIPTION

Elevation head switch 1a 1b, Yellow cap AC.DC220-240V

### SWITCHES AND LAMPS FEATURES

- Non Illuminated push button switches available with 12 different heads
- All switches complete with 1 NO and 1 NC contact blocks
- Mechanical life - 1 million operations
- Contact material - Silver Bifurcated and serrated
- Contact rating - AC12 Resistive / AC15 Electromagnetic - 240V (3A) / 415V (1.5A)
- Choice Of Cap colours
- Insulation resistance - >100M $\Omega$  @ 500VDC
- Different voltage ratings are available
- Operating Temperature -10 to +65°C

*Features may vary by product throughout the range.*

*Subject to technical modification without notice.*

*Typographical and other errors do not justify claim for damages.*

## SPECIFICATION

|  |                         |
|--|-------------------------|
| <b>Button Head Material</b>                | Polycarb VO             |
| <b>Body Material</b>                       | PA66 + 15% GF-VO        |
| <b>Locknut Material</b>                    | PA66 V2 +15%GF          |
| <b>Button Head Lamp Colour</b>             | Yellow                  |
| <b>Number of Contact Blocks</b>            | 2                       |
| <b>Shaft Style</b>                         | Standard                |
| <b>Max Wire Size Single Strand (Sq mm)</b> | 2.5                     |
| <b>Max Wire Size Multi Strand (Sq mm)</b>  | 1.5                     |
| <b>Min Temperature Rating °C</b>           | -10                     |
| <b>Max Temperature Rating °C</b>           | 65                      |
| <b>Panel Hole Size</b>                     | 22.5mm                  |
| <b>IP Rating</b>                           | 66                      |
| <b>Max Voltage (V)</b>                     | 220-240V                |
| <b>Product Sub Type</b>                    | Elevation head          |
| <b>Product Type</b>                        | Push button illuminated |
| <b>Terminal Type</b>                       | Screw clamp             |