


# Switches

## Range: Switches and Lamps

Order Code: DSS22-K211



### DESCRIPTION

Key 2 position selector 1a 1b

### SWITCHES AND LAMPS FEATURES

- Non Illuminated push button switches available with 12 different heads
- All switches complete with 1 NO and 1 NC contact blocks
- Mechanical life - 1 million operations
- Contact material - Silver Bifurcated and serrated
- Contact rating - AC12 Resistive / AC15 Electromagnetic - 240V (3A) / 415V (1.5A)
- Choice Of Cap colours
- Insulation resistance - >100M $\Omega$  @ 500VDC
- Different voltage ratings are available
- Operating Temperature -10 to +65°C

*Features may vary by product throughout the range.*

*Subject to technical modification without notice.*

*Typographical and other errors do not justify claim for damages.*

## SPECIFICATION

<b>Button Head Material</b>	Polycarb VO
<b>Body Material</b>	PA66 + 15% GF-VO
<b>Locknut Material</b>	PA66 V2 +15%GF
<b>Number of Contact Blocks</b>	2
<b>Selector Switch Positions</b>	2 Position 90 Degree
<b>Shaft Style</b>	Standard
<b>Max Wire Size Single Strand (Sq mm)</b>	2.5
<b>Max Wire Size Multi Strand (Sq mm)</b>	1.5
<b>Min Temperature Rating °C</b>	-10
<b>Max Temperature Rating °C</b>	65
<b>Panel Hole Size</b>	22.5mm
<b>IP Rating</b>	56
<b>Key Material</b>	Brass, Nickel Plated
<b>Product Sub Type</b>	Key 2 and 3 positions
<b>Product Type</b>	Selector and non-illuminated switches
<b>Terminal Type</b>	Screw clamp