


TeeTube

Range: Weatherproof/Waterproof Connectors

Order Code: THB.399.G4C.2





DESCRIPTION

TeeTube with innovative cable gland 4 Pole Screw - wp contact 7mm to 10.5mm on one gland 10.5mm to 14mm on the other 2 glands, 4 mm max conducter size IP68 32A 250V 3 cable entries

WEATHERPROOF/WATERPROOF CONNECTORS FEATURES

- Tough, robust construction with large cable range acceptance
- Straight through, T splitter and Y splitter versions available
- · Dual terminal versions available for easy fitting and looping of conductors (2+2 and 3+3 poles)
- Temperature rating of -40°C to +125°C Features may vary by product throughout the range.

Subject to technical modification without notice. Typographical and other errors do not justify claim for damages.



SPECIFICATION

Cable Entries	3
Max Current (A)	24
Max Voltage (V)	250
Number of Poles	4
Max Conductor Size (Sq mm)	2.5
Minimum Cable Diameter (mm)	7
Maximum Cable Diameter (mm)	14
IP Rating	68
Min Temperature Rating °C	-40
Max Temperature Rating °C	125
Temperature "T" Rating	T125
Body Material	PA66 / TPE
Fixing System	Cable
Terminal Type	Screw - wp
P Rating Min Temperature Rating °C Max Temperature Rating °C Femperature "T" Rating Body Material Fixing System	68 -40 125 T125 PA66 / TPE Cable

INDUSTRY ACCREDITATIONS



