

TeeTube

Range: Weatherproof/Waterproof Connectors

Order Code: THB.401.A3C



DESCRIPTION

TeeTube "L type" 2 Pole Screw - wp 7mm to 13.5mm, 2.5 mm max conducter size IP68 24A 450V 2 cable entries

WEATHERPROOF/WATERPROOF CONNECTORS FEATURES

- Tough, robust construction with large cable range acceptance
- Straight through, T splitter and Y splitter versions available
- Dual terminal versions available for easy fitting and looping of conductors (2+2 and 3+3 poles)
- Temperature rating of -40°C to +125°C

Features may vary by product throughout the range.

Subject to technical modification without notice. Typographical and other errors do not justify claim for damages.

hylec

MAKING THE RIGHT CONNECTIONS

SPECIFICATION

Cable Entries	2
Max Current (A)	24
Max Voltage (V)	450
Number of Poles	2
Max Conductor Size (Sq mm)	2.5
Minimum Cable Diameter (mm)	7
Maximum Cable Diameter (mm)	13.5
IP Rating	68
Min Temperature Rating °C	-40
Max Temperature Rating °C	125
Temperature "T" Rating	T85
Body Material	PA66 / TPE
Fixing System	Cable
Terminal Type	Screw - wp

INDUSTRY ACCREDITATIONS



MAKING THE RIGHT CONNECTIONS WWW.HYLEC-APL.COM | SALES@HYLEC-APL.COM | 01933 234400

