

# **TeeTube**

### Range: Weatherproof/Waterproof Connectors

Order Code: THB.401.E4A.1





### DESCRIPTION

TeeTube "L type" 4 Pole Screw - end barrier 7mm to 13.5mm on one gland 7mm to 10.5mm on the other gland, 1.5mm max conducter size IP68 32A 450V 2 cable entries

### WEATHERPROOF/WATERPROOF CONNECTORS FEATURES

- Tough, robust construction with large cable range acceptance
- Straight through, T splitter and Y splitter versions available
- Dual terminal versions available for easy fitting and looping of conductors (2+2 and 3+3 poles)
- Temperature rating of -40°C to +125°C

Features may vary by product throughout the range.

Subject to technical modification without notice. Typographical and other errors do not justify claim for damages.

## hylec

### MAKING THE RIGHT CONNECTIONS

#### **SPECIFICATION**

Cable Entries	2
Max Current (A)	32
Max Voltage (V)	450
Number of Poles	4
Max Conductor Size (Sq mm)	4
Minimum Cable Diameter (mm)	7
Maximum Cable Diameter (mm)	10.5
IP Rating	68
Min Temperature Rating °C	-40
Max Temperature Rating °C	125
Temperature "T" Rating	T125
Body Material	PA66 / TPE
Fixing System	Cable
Terminal Type	Screw - end barrier contact

### **INDUSTRY ACCREDITATIONS**



MAKING THE RIGHT CONNECTIONS WWW.HYLEC-APL.COM | SALES@HYLEC-APL.COM | 01933 234400

